



**SUMMARY TEST DATA  
ON  
BPF-4G-4G-CD-SFF**

Customer: \_\_\_\_\_ Tested By: J. Peacher  
SO No: \_\_\_\_\_ Temperature: +25°C  
Model No: BPF-4G-4G-CD-SFF Date: 12/6/18  
Serial No: PL24004/1849 Drawing No: 27635300 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	PASSBAND FREQUENCY:	2.0 TO 6.0 GHz	2.0 TO 6.0 GHz	PMI QA 1	
2	PASSBAND BANDWIDTH:	3 dB	Pass		
3	PASSBAND VSWR:	1.5:1 MAXIMUM	Pass		
4	PASSBAND INSERTION LOSS:	1.0 dB MAXIMUM	Pass		
5	PASSBAND RIPPLE:	0.5 dB MAXIMUM P-P	Pass		
6	REJECTION @ DC TO 1.7 GHz:	65 dB MINIMUM	Pass		
7	REJECTION ABOVE 6.7 GHz:	65 dB MINIMUM	Pass		
8	POWER HANDLING:	2 W CW MINIMUM	Pass		PMI QA 1

QA/QC Approval:  PMI QA 1 Date: 12/6/18

7311-F Grove Road, Frederick, MD 21704 USA  
Phone: (301) 662-5019 Fax: (301) 662-1731  
Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)