



**SUMMARY TEST DATA
ON
TD-1G12G-RL-CD-SFF**

PL24616/1908

Customer: _____ Tested By: Simon K.
SO No: _____ Temperature: +25°C
Model No: TD-1G12G-RL-CD-SFF Date: 02/21/19
Serial No: PL24616/1908 Drawing No: 27623443 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	PASS FAIL	QA QC
1	Frequency Range:	1 TO 12.0 GHz Minimum	1 TO 12.0 GHz See Plot	PMI QA 1
2	VSWR:	3.0: 1 Typical	2.21 : 1 See Plot	
3	Dynamic Range:	-30dBm to +10dBm	-30dBm to +10dBm	
4	Threshold Variation: (with Frequency)	± 1.5 dB Maximum	± 0.60 dB	
5	Propagation Delay	10ns Typical 3dB above Threshold Setting (50% RF Input to 50% Logic at -10dBm)	11 ns See Typical Characteristics	
6	Min Pulse Width:	50 ns Typical	50 ns	
7	Output	TTL 0: Input Power > Threshold Setting TTL 1: Otherwise	Pass	
8	Temperature Stability	1.0 dB Typical 3 dB Above Threshold Setting	Pass	
9	Threshold Setting Control:	0 to +5 Volts	0 to +5 Volts	
10	Threshold Level Setting Range:	-30 to -10 dBm	-30 to -9.5 dBm	
11	Maximum Input Power:	100 mW CW	Pass	
12	DC Supply:	+5 VDC @ 100mA Typical -5 VDC @ 100mA Typical	+5 VDC @ 72.8 mA -5 VDC @ 27.7 mA	PMI QA 1

QA/QC Approval: _____

PMI
QA 1

Date: _____

2/22/19



SUMMARY TEST DATA
ON
TD-1G12G-RL-CD-SFF

PL24616/1908

VSWR @ 25C

