



SUMMARY TEST DATA ON ISO-108M118M-20-NFF

CUSTOMER: _____
SO: _____
MODEL NO: ISO-108M118M-20-NFF
SERIAL NO: PL24723/1905

TESTED BY: Garrett Radtke
TEMPERATURE: +25°C
DATE: 1/31/2019
DRAWING NO: 27636080 REV: A1

| TEST ITEM NO: | PARAMETERS | SPECIFIED VALUE | MEASURED VALUE | REMARKS QA/QC |
|---------------|-----------------|--------------------|--------------------|-----------------|
| 1 | Frequency Range | 108 MHz to 118 MHz | 108 MHz to 118 MHz | PMI QA1 |
| 2 | Insertion Loss | 0.6 dB MAX. | 0.54 dB | |
| 3 | Isolation | 20 dB MIN. | 18.65dB | CUSTOMER WAVIER |
| 4 | VSWR | 1.2:1 MAX. | 1.23 | CUSTOMER WAVIER |
| 5 | Forward Power | 60W MAX. | 60W MAX. | PMI QA1 |
| 6 | Reverse Power | 60W MAX. | 60W MAX. | |

QA/QC Approval: PMI QA1

Date: 2/1/19

INSERTION LOSS, ISOLATION, AND VSWR

