



**SUMMARY TEST DATA  
ON  
PEC4-16-8G18G-4R7-18-15-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: PEC4-16-8G18G-4R7-18-15-SFF  
 Serial Pair: PL24815/1906

Tested By: K. Mansfield  
 Temperature: +25°C  
 Date: 2/6/2019  
 Drawing No: 27628813      REV: B1



TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC	
1	Frequency Range:	8.0 to 18.0 GHz	8.0 to 18.0 GHz	PMI QA 1	
2	Gain:	16 dB Max. 13 dB Min.	15.5 dB Max. 13.4 dB Min. See Plot		
3	Gain Flatness:	±1.5 dB Max.	0.97 dB -1.11 dB See Plot		
4	Noise Figure:	4.7 dB Max.	4.46 dB See Plot		
5	OP1dB:	+18 dBm Typ.	+20.4 dB See Plot		
6	VSWR: (Input/Output)	1.67:1 Max. Input 2.25:1 Max. Output	1.25:1 In 1.4:1 Out See Plot		
7	Maximum Input:	+30 dBm CW	Pass See Typical Characteristics		
8	DC Supply:	+12.5 to +28 VDC @ 250 mA Typ..	+12 VDC @ 209 mA		PMI QA 1

QA/QC Approval:       PMI QA 1      Date: 2/6/19



**SUMMARY TEST DATA  
ON  
PEC4-16-8G18G-4R7-18-15-SFF**

PL24815/1906





# SUMMARY TEST DATA ON PEC4-16-8G18G-4R7-18-15-SFF

PL24815/1906

