



SUMMARY TEST DATA
ON
PS-360-3237-8-292FF

Customer: _____
Job No: _____
Model No: PS-360-3237-8-292FF
Serial No: PL25479/1917

Tested By: K. Mansfield
Temp: +25°C
Date: Thursday, May 02, 2019
Drawing No: 27617037 Rev: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	32 GHz to 37 GHz	32 GHz to 37 GHz	PMI QA 1	
2	Insertion Loss:	13.0 dB Typ.	15 dB See Plot		
3	VSWR Input: (J2)	2.0:1 Typ. 2.3:1 Max.	1.8:1		
4	VSWR Output: (J1)	2.5:1 Typ. 3.0:1 Max.	2.6:1		
5	Step Size: (LSB)	1.40625°	1.26668°		
6	Phase Shift: (Max.)	358.59375°	354.20143°		
7	Amplitude Error:	±1.50 dB Typ.	±1.8 dB		
8	Phase Shift Error:	±5.0° Typ.	+0.1° -2.2° See Plot		
9	Switching Speed: (10% to 90% of Phase Shift)	500 ns Max.	<300 ns See Typical Characteristics		
10	Voltage:	+15 V @ 90 mA Max. -15 V @ 60 mA Max.	+15 V @ 14 mA -15 V @ 9 mA		PMI QA 1

QA/QC Approval:  _____
PMI
QA 1

Date: 5/2/19



SUMMARY TEST DATA ON PS-360-3237-8-292FF

PL25479/1917

