



**SUMMARY TEST DATA
ON
PS-360-3237-8-292FF**

Customer: _____
 Job No: _____
 Model No: PS-360-3237-8-292FF
 Serial No: PL25480/1917

Tested By: K. Mansfield
 Temp: +25°C
 Date: Thursday, May 02, 2019
 Drawing No: 27617037 Rev: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	32 GHz to 37 GHz	32 GHz to 37 GHz	PMI QA 1	
2	Insertion Loss:	13.0 dB Typ.	14.5 dB See Plot		
3	VSWR Input: (J2)	2.0:1 Typ. 2.3:1 Max.	1.8:1		
4	VSWR Output: (J1)	2.5:1 Typ. 3.0:1 Max.	2.5:1		
5	Step Size: (LSB)	1.40625°	1.46664°		
6	Phase Shift: (Max.)	358.59375°	357.88158°		
7	Amplitude Error:	±1.50 dB Typ.	±1.7 dB		
8	Phase Shift Error:	±5.0° Typ.	+0.3° -0.8° See Plot		
9	Switching Speed: (10% to 90% of Phase Shift)	500 ns Max.	<300 ns See Typical Characteristics		
10	Voltage:	+15 V @ 90 mA Max. -15 V @ 60 mA Max.	+15 V @ 14 mA -15 V @ 9 mA		PMI QA 1

QA/QC Approval: *[Signature]* PMI QA 1

Date: 5/2/19



**SUMMARY TEST DATA
ON
PS-360-3237-8-292FF**

PL25480/1917

