



**SUMMARY TEST DATA
ON
P2T-500M18G-80-T-55-SFF-1**

Customer: _____
 SO No: _____
 Model No: P2T-500M18G-80-T-55-SFF-1
 Serial No: PL25483/1917

Tested By: E. Kretz
 Temperature: +25° C
 Date: 4/26/2019
 Drawing No: 27624509 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	0.5 to 18.0 GHz	0.5 to 18.0 GHz	PMI QA 1
2	Insertion Loss:	3.5 dB Max.	3 dB See Plot	
3	Isolation:	80 dB Typ.	80 dB See Plot	
4	VSWR:	2:1 Max.	1.8:1 See Plot	
5	Switching Speed:	50% TTL to 10%/90% RF 25 ns Typ.	<40 ns See Typical Characteristics	
6	Input Power:	+20 dBm CW	Pass See Typical Characteristics	
7	Survival Power:	+23 dBm CW	Pass See Typical Characteristics	
7	Control:	TTL LOGIC "0" = J1-J2 ON TTL LOGIC "1" = J1-J3 ON	Pass	
8	Power Supply:	+5 V @ 65 mA Max. -5 V @ 50 mA Max.	13 mA 67 mA	

QA/QC Approval: _____

PMI
QA 1

Date: _____

4/29/19



SUMMARY TEST DATA ON P2T-500M18G-80-T-55-SFF-1

PL25483/1917

