



**SUMMARY TEST DATA  
ON  
P4T-6G18G-27-T-SFF**

PL25566/1919

Customer: \_\_\_\_\_ Tested By: B. Willard  
 SO No: \_\_\_\_\_ Temperature: +25°C  
 Model No: P4T-6G18G-27-T-SFF Date: 01/24/2020  
 Serial No: PL25566/1919 Drawing No: 27633410 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC																																																																		
1	Frequency Range:	6.0 TO 18.0 GHz	6.0 TO 18.0 GHz (See Plots)	PMI QA1																																																																		
2	Insertion Loss	2.5 dB MAX @ 6.0 GHz TO 8.0 GHz 3.7 dB MAX @ 8.0 GHz TO 12.4 GHz 4.8 dB MAX @ 12.4 GHz TO 18.0 GHz	2.3dB MAX @ 6.0 GHz TO 8.0 GHz 2.7dB MAX @ 8.0 GHz TO 12.4 GHz 3.7dB MAX @ 12.4 GHz TO 18.0 GHz (See Plots)	PMI QA1																																																																		
3	Isolation (On/All Ports Off)	45 dB MIN @ 6.0 GHz TO 8.0 GHz 27 dB MIN @ 8.0 GHz TO 18.0 GHz	75dB MIN 61dB MAX (See Plots)																																																																			
4	VSWR	2.3:1 MAX @ 6.0 GHz TO 12.4 GHz 2.0:1 MAX @ 12.4 GHz TO 18.0 GHz	1.93:1 (See Plots)																																																																			
5	RF Impedance:	50 Ω	50 Ω																																																																			
6	Switching Speed (ON/OFF):	500 ns MAX (FROM 50% TTL TO 90%/10% RF VOLTAGE)	Switching Speed (ON) 50 ns Switching Speed (OFF) 25 ns (See Typical Characteristics)																																																																			
7	Power Supply:	+5.0 VDC ±5% @ 100 mA MAX -15.0 VDC ±5% @ 60 mA MAX	+5.0 VDC ±5% @ 97 mA -15.0 VDC ±5% @ 30 mA																																																																			
8	Control Logic	LOGIC "0" = -0.3 V TO +0.8 V FOR PORT ON (LOW LOSS STATE) LOGIC "1" = +2.0 V TO +5.0 V FOR PORT OFF (ISOLATION STATE)  <table border="1"> <thead> <tr> <th colspan="8">LOGIC TABLE (J1: COMMON PORT)</th> </tr> <tr> <th rowspan="2">PORT</th> <th colspan="4">TTL INPUT LEVEL</th> <th rowspan="2">J1-J2</th> <th rowspan="2">J1-J3</th> <th rowspan="2">J1-J5</th> <th rowspan="2">J1-J6</th> </tr> <tr> <th>E2</th> <th>E3</th> <th>E5</th> <th>E6</th> </tr> </thead> <tbody> <tr> <td>J2</td> <td>0</td> <td>1</td> <td>1</td> <td>1</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> </tr> <tr> <td>J3</td> <td>1</td> <td>0</td> <td>1</td> <td>1</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> </tr> <tr> <td>J5</td> <td>1</td> <td>1</td> <td>0</td> <td>1</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> </tr> <tr> <td>J6</td> <td>1</td> <td>1</td> <td>1</td> <td>0</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> <td>ISOLATION LOSS</td> </tr> <tr> <td>ALL OFF</td> <td>1</td> <td>1</td> <td>1</td> <td>1</td> <td colspan="4">ISOLATION</td> </tr> </tbody> </table>	LOGIC TABLE (J1: COMMON PORT)								PORT	TTL INPUT LEVEL				J1-J2	J1-J3	J1-J5	J1-J6	E2	E3	E5	E6	J2	0	1	1	1	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	J3	1	0	1	1	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	J5	1	1	0	1	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	J6	1	1	1	0	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ALL OFF	1	1	1	1	ISOLATION				Pass	PMI QA1
LOGIC TABLE (J1: COMMON PORT)																																																																						
PORT	TTL INPUT LEVEL				J1-J2	J1-J3	J1-J5	J1-J6																																																														
	E2	E3	E5	E6																																																																		
J2	0	1	1	1	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS																																																														
J3	1	0	1	1	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS																																																														
J5	1	1	0	1	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS																																																														
J6	1	1	1	0	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS	ISOLATION LOSS																																																														
ALL OFF	1	1	1	1	ISOLATION																																																																	

\*: 1 μs MAXIMUM PULSE WIDTH  
 2: A UNIT LOAD IS 2.0 mA SINK CURRENT AND 50 μA SOURCE CURRENT

QA/QC Approval:  PMI QA1 Date: 1/27/20


7311-F Grove Road, Frederick, MD 21704 USA  
 Phone: (301) 662-5019 Fax: (301) 662-1731  
 Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)




**SUMMARY TEST DATA  
ON  
P4T-6G18G-27-T-SFF**

PL25566/1919

**(J1 – J2) Insertion Loss and Return Loss**



**(J1 – J3) Insertion Loss and Return Loss**




7311-F Grove Road, Frederick, MD 21704 USA  
Phone: (301) 662-5019 Fax: (301) 662-1731  
Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)




**SUMMARY TEST DATA  
ON  
P4T-6G18G-27-T-SFF**

PL25566/1919

**(J1 – J4) Insertion Loss and Return Loss**



**(J1 – J5) Insertion Loss and Return Loss**




7311-F Grove Road, Frederick, MD 21704 USA  
 Phone: (301) 662-5019 Fax: (301) 662-1731  
 Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)




**SUMMARY TEST DATA  
ON  
P4T-6G18G-27-T-SFF**

PL25566/1919

**(J1 – J2) Isolation and Termination Return Loss**



**(J1 – J3) Isolation and Termination Return Loss**



7311-F Grove Road, Frederick, MD 21704 USA  
Phone: (301) 662-5019 Fax: (301) 662-1731  
Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)



**SUMMARY TEST DATA  
ON  
P4T-6G18G-27-T-SFF**

PL25566/1919

**(J1 – J4) Isolation and Termination Return Loss**



**(J1 – J5) Isolation and Termination Return Loss**



7311-F Grove Road, Frederick, MD 21704 USA  
Phone: (301) 662-5019 Fax: (301) 662-1731  
Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)