



**SUMMARY TEST DATA
ON
P1T-6G18G-60-T-SFF-1W**

Customer: _____ Tested By: L. McGraw
SO No: _____ Temperature: +25°C
Model No: P1 T-6G18G-60-T-SFF-1W Date: 09/16/19
Serial No: PL26515/1937 Drawing No: 27628521 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	6.0 to 18.0 GHz	6.0 to 18.0 GHz	PMI QA 1
2	Insertion Loss:	2.75dB Max	2.41dB (See Plot)	
3	Isolation:	65dB Min	84dB (See Plot)	
4	VSWR:	2.0:1 Max (1.5:1 Goal)	1.8:1	
5	Switching Speed:	25ns Typ	<25ns See Typical Characteristics	
6	Operating Power:	+30dBm Max	+30dBm See Typical Characteristics	
7	Control	TTL Logic "0" = Insertion Loss "1" = Isolation	Pass	
8	Power Supply:	+5VDC @ 50mA Max -15VDC @ 75mA Max	40 mA 70 mA	PMI QA 1


QA/QC Approval:  PMI QA 1 Date: 9/17/19

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com



**SUMMARY TEST DATA
ON
P1T-6G18G-60-T-SFF-1W**

(J1-J2) Insertion Loss and Return Loss



(J1 - J2) Isolation and Termination Return Loss

