



**SUMMARY TEST DATA  
ON  
4BP160-5-2A-PP**

**PL26630/1939**

Customer: \_\_\_\_\_ Tested By: C. Ertter  
SO No: \_\_\_\_\_ Temperature: +25°C  
Model No: 4BP160-5-2A-PP Date: 09/26/19  
Serial No: PL266230/1939 Drawing No: 27608446 Rev: A1

| TEST.<br>ITEM NO | PARAMETERS                    | SPECIFIED VALUE     | TEST<br>RESULTS                | QA<br>QC   |
|------------------|-------------------------------|---------------------|--------------------------------|------------|
| 1                | Center<br>Frequency:          | 160 MHz $\pm$ 0.23% | 160.14 MHz<br>See Plot         | PMI<br>QA1 |
| 2                | 3 dB Bandwidth:               | 20 MHz $\pm$ 5%     | 4.83 MHz<br>See Plot           |            |
| 3                | Insertion Loss:<br>(Passband) | 5 dB Nominal        | 7.95 dB<br>See Plot            |            |
| 4                | Rejection                     | 4 Section Response  | 4 Section Response<br>See Plot |            |
| 5                | VSWR in The Passband:         | 1.5:1 Max           | < 1.5:1<br>See Plot            | PMI<br>QA1 |

QA/QC Approval: \_\_\_\_\_

PMI  
QA1

Date: \_\_\_\_\_

9/27/19



**SUMMARY TEST DATA  
ON  
4BP160-5-2A-PP**

**PL26630/1939**

PL26630/1939

