



SUMMARY TEST DATA
ON
P3T-2G8G-70-T-SFF

Customer: _____
SO No: _____
Model No: P3T-2G8G-70-T-SFF
Serial No: PL26778/1942

Tested By: B. Willard
Temperature: +25°C
Date: 10/17/2019
Drawing No: 26936360 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2.0 GHz - 8.0 GHz	2.0 GHz - 8.0 GHz	
2	Insertion Loss:	2.1 dB Max.	2.1 dB See Plot	
3	Isolation:	70 dB Min.	84 dB See Plot	
4	VSWR: In/Out	1.7:1 Max.	In 1.7:1 Out 1.64 :1 See Plot	
5	Switching Speed:	180 ns Max.	ON : 30 ns OFF : 21.9 ns	
6	DC Supply:	+12 VDC @ 85 mA -12 VDC @ 85 mA	+5 VDC @ 79mA -12 VDC @ 45mA	
7	Control Signal:	TTL "0" → (ISOLATION) TTL "1" → (LOW LOSS)	Pass	
8	Input Power:	+20 dBm MAX	Pass	

QA/QC Approval: _____

Date: _____



SUMMARY TEST DATA ON P3T-2G8G-70-T-SFF

PL26778/1942

