



**SUMMARY TEST DATA
ON
P3T-2G8G-70-T-SFF**

Customer: _____
 SO No: _____
 Model No: P3T-2G8G-70-T-SFF
 Serial No: PL27125/1946

Tested By: L. McGraw
 Temperature: +25°C
 Date: 11/13/2019
 Drawing No: 27636360 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC		
1	Frequency Range:	2.0 GHz - 8.0 GHz	2.0 GHz - 8.0 GHz			
2	Insertion Loss:	2.1 dB Max.	2.09 dB See Plot			
3	Isolation:	70 dB Min.	82 dB See Plot			
4	VSWR: In/Out	1.7:1 Max.	In 1.49:1 Out 1.37 :1 See Plot			
5	Switching Speed:	180 ns Max.	ON: 30ns OFF: 21.9ns			
6	DC Supply:	+5 VDC @ 85 mA Max. -12 VDC @ 85 mA Max.	+5 VDC @ mA -12 VDC @ mA			
7	Control Signal:	Control Input			Pass	
		E1	E2	E3		Signal
		High	Low	Low		J0-J1
		Low	High	Low		J0-J2
		Low	Low	High	J0-J3	

QA/QC Approval: _____

Date: 11/14/19



SUMMARY TEST DATA
ON
P3T-2G8G-70-T-SFF

PL27125/1946

