



SUMMARY TEST DATA ON DTA-0R4G18G-60-CD-1

Customer: _____
 Job No: _____
 Model No: DTA-0R4G18G-60-CD-1
 Serial No: PL27504/2003

Tested By: K. Mansfield
 Date: Tuesday, January 14, 2020
 Temperature: +25° C
 Drawing No: 27637160 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	RESULTS	QA QC	
1	Frequency Range:	0.4 GHz – 18 GHz	0.4 GHz – 18 GHz	PMI QA1	
2	Insertion Loss:	4.8 dB Max.	3.6 dB See Plot		
3	VSWR:	2.0:1 Max.	1.9:1 See Plot		
4	Flatness to 20 dB:	± 1.0 dB Typ.	±0.47 dB See Plot		
6	Flatness to 40 dB:	± 1.25 dB Typ.	±0.98 dB See Plot		
7	Flatness to 60 dB:	± 3.0 dB Typ.	±4.2 dB See Plot		
8	Accuracy of Attenuation 0 to 20 dB:	± 1.0 dB Typ.	±0.07 dB See Plot		
9	Accuracy of Attenuation 20 to 40 dB:	± 1.5 dB Typ.	±0.1 dB See Plot		
10	Accuracy of Attenuation 40 to 60 dB:	± 2.0 dB Typ.	±0.16 dB See Plot		
11	Switching Speed:	1.0 µs Max. On 0.5 µs Max. Off	< 1.0 us See Typical Characteristics		
12	DC Supply:	+15VDC @ 150 mA	111 mA		PMI QA1

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
0.0625	0.03	0.04	0.01
0.125	0.12	0.01	0.01
0.25	0.25	0.00	0.02
0.50	0.50	0.00	0.04
1.00	1.01	-0.01	0.09
2.00	2.01	-0.01	0.16
4.00	4.03	-0.03	0.30
8.00	8.06	-0.06	0.44
16.00	16.07	-0.06	0.45
32.00	32.06	-0.06	0.77
62.00	61.87	0.13	5.05
63.94	64.20	-0.26	6.24

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
5.00	5.01	-0.01	0.35
10.00	10.06	-0.06	0.44
15.00	15.00	0.00	0.44
20.00	20.05	-0.05	0.47
25.00	25.03	-0.03	0.62
30.00	30.07	-0.07	0.73
35.00	35.07	-0.07	0.82
40.00	40.10	-0.10	0.98
45.00	45.03	-0.03	1.46
50.00	50.16	-0.16	1.79
55.00	55.08	-0.08	2.70
60.00	60.03	-0.03	4.20

QA/QC Approval: *[Signature]* PMI
QA1

Date: 1/15/20



SUMMARY TEST DATA ON DTA-0R4G18G-60-CD-1

PL27504/2003

