



SUMMARY TEST DATA ON DTA-2G18G-60-12-CD-1-20DBM-TS

Customer: _____
 Job No: _____
 Model No: DTA-2G18G-60-12-CD-1-20DBM-TS
 Serial No: PL28092/2011

Tested By: K. Mansfield
 Date: Tuesday, March 10, 2020
 Temperature: +25° C
 Drawing No: 27617795 Rev: A2

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	PASS/FAIL	QA QC
1	Frequency Range:	2 GHz – 18 GHz	2 GHz – 18 GHz	
2	Insertion Loss:	4.8 dB Max.	3.6 dB See Plot	
3	VSWR:	2.0:1 Max.	1.88:1 See Plot	
4	Flatness to 20 dB:	± 1.0 dB Typ.	0.47 dB See Plot	
6	Flatness to 40 dB:	± 1.25 dB Typ.	0.74 dB See Plot	
7	Flatness to 60 dB:	± 3.0 dB Typ.	0.87 dB See Plot	
8	Accuracy of Attenuation 0 to 20 dB:	± 1.0 dB Typ.	0.05 dB See Plot	
9	Accuracy of Attenuation 20 to 40 dB:	± 1.5 dB Typ.	0.16 dB See Plot	
10	Accuracy of Attenuation 40 to 60 dB:	± 2.0 dB Typ.	0.23 dB See Plot	
11	Temp. Sensor:	10mV/°C, 3.0V @ 25°C	3 V	
12	Switching Speed:	On Time: 1.0 µs Max. Off Time: 0.5 µs Max.	<1.0 µs On Time <0.5 µs Off Time See Typical Characteristics	
13	DC Supply:	+15VDC @ 150 mA Max.	120 mA	

Programed Attenuation: dB	Attenuation dB	Accuracy of Attenuation dB	Flatness dB ±dB
0.0156	0.0108	0.00	0.01
0.0313	0.0264	0.00	0.01
0.0625	0.0542	0.01	0.01
0.125	0.119	0.01	0.01
0.25	0.25	0.00	0.02
0.50	0.49	0.01	0.03
1.00	1.00	0.00	0.05
2.00	1.99	0.01	0.10
4.00	4.00	0.00	0.18
8.00	8.00	0.00	0.27
16.00	15.98	0.07	0.35
32.00	31.93	0.07	0.73

Programed Attenuation dB	Attenuation dB	Accuracy of Attenuation dB	Flatness dB ±dB
5.00	4.95	0.05	0.21
10.00	10.01	-0.01	0.31
15.00	14.95	0.05	0.35
20.00	19.98	0.02	0.47
25.00	24.90	0.10	0.66
30.00	29.92	0.08	0.74
35.00	34.84	0.16	0.72
40.00	39.87	0.13	0.62
45.00	44.83	0.17	0.48
50.00	49.79	0.21	0.41
55.00	54.77	0.23	0.62
60.00	59.84	0.16	0.87

QA/QC Approval: *[Signature]*

Date: 3/13/2020



SUMMARY TEST DATA ON DTA-2G18G-60-12-CD-1-20DBM-TS

PL28092/2011

