



SUMMARY TEST DATA ON DTA-13G14G-40-8-CD-1-20DBM

Customer: _____
 Job No: _____
 Model No: DTA-13G14G-40-8-CD-1-20DBM
 Serial No: PL28195/2012

Tested By: K. Mansfield
 Date: Tuesday, March 24, 2020
 Temperature: +25° C
 Drawing No: 27636480 Rev: A1

Test Item No.	Parameters	Specified Value	Test Results	QA QC	
1	Frequency Range:	13 GHz – 14 GHz	13 GHz – 14 GHz	PMI QA 1	
2	Insertion Loss:	5.0 dB Max.	3.1 dB See Plot		
3	VSWR:	2.0:1 Max.	1.7:1 See Plot		
4	Step Size:	0.25 dB (LSB)	0.25 dB		
5	Adjustment Step Size Accuracy:	± 0.125 dB	± 0.098 dB		
6	Phase Variation Vs Attenuation Step Size:	1.5° / dB Typ. 2.0° / dB Max.	1.2° / dB		
7	Input 0.1 dB Compression Point:	+20 dBm Min.	> +20 dBm		
8	Monotonicity:	Guaranteed	Pass		
9	Switching Speed:	1.0 µs Max. On 0.5 µs Max Off	< 0.5 µs On < 0.4 µs Off See Typical Characteristics		
10	DC Power Supply:	+12 V @ 150 mA Max.	144 mA		PMI QA 1

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
0.25	0.25	0.00	0.01
0.50	0.49	0.01	0.01
1.00	0.99	0.01	0.02
2.00	1.99	0.01	0.05
4.00	3.98	0.02	0.08
8.00	7.99	0.01	0.11
16.00	15.99	0.01	0.13
32.00	31.93	0.07	0.14

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
5.00	4.86	0.14	0.08
10.00	9.99	0.01	0.12
15.00	14.93	0.07	0.13
20.00	19.99	0.01	0.13
25.00	24.92	0.08	0.14
30.00	29.96	0.04	0.15
35.00	34.96	0.04	0.11
40.00	39.91	0.09	0.11

QA/QC Approval:

PMI
QA 1

Date: 3/24/20



SUMMARY TEST DATA ON DTA-13G14G-40-8-CD-1-20DBM

PL28195/2012

