



SUMMARY TEST DATA ON SC00066-06 REV C

Customer: _____
SO No: _____
Model No: SC00066-06 REV C
Serial No: PL29512/2027
Part No: _____

Tested By: M. Hanken
Temperature: 25 Degrees C
Date: 7/5/2020
Drawing No: 27609928

REV: B1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	0.1 to 20.25 GHz	0.1 to 20.25 GHz	
2	Gain:	19.5 dB Min. 23.5 dB Max.	+20.4 dB Min. +21.3 dB Max. See Plot	
3	Gain Flatness:	±0.5 dB Max. (Over any 500 MHz span over Full Band)	±0.17 dB See Plot	
4	Noise Figure:	6.0 dB Max. (0.1 to 19 GHz) 6.5 dB Max. (19 to 20.25 GHz)	5.6 dB (0.1 to 19 GHz) 4.3 dB (19 to 20.25 GHz) See Plot	
5	Max Input Power:	+20 dBm (Without Damage)	+20 dBm	
6	VSWR: (Input/Output)	Input: 2.5:1 Max. Output: 2.0:1 Max.	Input: 2.2:1 Output: 1.7:1 See Plot	
7	Output IP3:	+24 dBm Min.	≥24 dBm See Typical Characteristics	
8	OP1dB:	+14 dBm Min.	≥14 dBm See Typical Characteristics	
9	Reverse Isolation:	30 dB Min.	-64 dB See Plot	
10	DC Supply:	+15 VDC ±5% @ 275 mA Max.	+15 VDC @ 168 mA	

QA/QC Approval: _____


Date: _____




SUMMARY TEST DATA ON SC00066-06 REV C

PL29512/2027


Gain



Gain Flatness Full Band



Gain Flatness any 500 MHz Span







SUMMARY TEST DATA ON SC00066-06 REV C

PL29512/2027

Noise Figure



VSWR



Reverse Isolation

