



**SUMMARY TEST DATA
ON
IAW MACOM SC00066-06 REV C**

Customer: _____
SO No: _____
Model No: IAW MACOM SC00066-06 REV C
Serial No: PL29512/2027
Part No: _____

Tested By: John R
Temperature: 25 Degrees C
Date: 5/4/2021
Drawing No: 27609928 REV: B1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	0.1 to 20.25 GHz	0.1 to 20.25 GHz	PMI QA 2
2	Gain:	19.5 dB Min. 23.5 dB Max.	+20.2 dB Min. +21.8 dB Max. See Plot	
3	Gain Flatness:	±0.5 dB Max. (Over any 500 MHz span over Full Band)	±0.25 dB See Plot	
4	Noise Figure:	6.0 dB Max. (0.1 to 19 GHz) 6.5 dB Max. (19 to 20.25 GHz)	5.6 dB (0.1 to 19 GHz) 4.4 dB (19 to 20.25 GHz) See Plot	
5	Max Input Power:	+20 dBm (Without Damage)	+20 dBm	
6	VSWR: (Input/Output)	Input: 2.5:1 Max. Output: 2.0:1 Max.	Input: 2.3:1 Output: 1.8:1 See Plot	
7	Output IP3:	+24 dBm Min.	≥24 dBm See Typical Characteristics	
8	OP1dB:	+14 dBm Min.	≥14 dBm See Typical Characteristics	
9	Reverse Isolation:	30 dB Min.	58 dB See Plot	
10	DC Supply:	+15 VDC ±5% @ 275 mA Max.	+15 VDC @ 150 mA	PMI QA 2

QA/QC Approval: _____

PMI
QA 2




Date: 5/4/21

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com



**SUMMARY TEST DATA
ON
IAW MACOM SC00066-06 REV C**

PL29512/2027



7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com



SUMMARY TEST DATA ON IAW MACOM SC00066-06 REV C

PL29512/2027

