



**SUMMARY TEST DATA  
ON  
PDC-2G18G-20C-SFF-50W**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: PDC-2G18G-20C-SFF-50W  
 Serial No: PL29558/2027

Tested By: M. Hanken  
 Temperature: +25°C  
 Date: 7/3/2020  
 Drawing No: 27638200 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 to 18 GHz	2.0 to 18 GHz	PMI QA 2	
2	Insertion Loss (Excluding coupling loss 0.04 dB)	0.7 dB MAX.	0.46 dB (See Plot)		
3	VSWR:	Primary: 1.40:1 MAX Secondary: 1.40:1 MAX	1.28:1 (See Plot)		
4	Directivity:	15 dB MIN.	17.3 dB See Plot		
5	Coupling:	20 ± 0.7 dB MAX.	20 ± 0.54 dB See Plot		
6	Frequency Sensitivity:	≤ ±0.7 dB Over Frequency	+0.27 dB (See Plot)		
7	Power Handling:	Incident: 50 Watts MAX Reflected: 2 Watts MAX	Incident 50 Watts MAX Reflected 2 Watts MAX See Typical Characteristics		
8	Impedance:	50 Ω	50 Ω		PMI QA 2

QA/QC Approval: *[Signature]* PMI  
QA 2

Date: 7/3/20



# SUMMARY TEST DATA ON PDC-2G18G-20C-SFF-50W

PL29558/2027

