



SUMMARY TEST DATA ON P4T-2G18G-70-T-SFF

PL30122/2036

Customer: _____

SO No: _____

Tested By: John R

Temperature: 25 Degrees C

Model No: P4T-2G18G-70-T-SFF

Date: 9/22/2020

Serial No: PL30122/2036

Drawing No: 27635280

Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2.0 GHz to 18.0 GHz	2.0 GHz to 18.0 GHz	PMI QA 2
2	Insertion Loss:	3.5 dB Max.	3.4 dB See Plot	
3	Isolation:	70 dB Min	70 dB See Plot	
4	VSWR: In/Out	2.0:1 Max.	1.7:1 In 1.9:1 Out See Plots	
5	Input Power:	+30 dBm Max. (Survival) +20 dBm Max. (Operational)	Pass See Typical Characteristics	
6	Switching Speed:	100 ns Max.	Pass See Typical Characteristics	
7	DC Supply:	+5 VDC @ 200 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 112 mA -15 VDC @ 54 mA	
8	Control Signal:	TTL Logic "0" = Low Loss TTL Logic "1" = Isolation E1 Controls J1-J2 E2 Controls J1-J3 E3 Controls J1-J4 E4 Controls J1-J5	Pass	

QA/QC Approval: PMI QA 2


Date: 9/24/20

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com



SUMMARY TEST DATA ON P4T-2G18G-70-T-SFF

PL30122/2036





SUMMARY TEST DATA ON P4T-2G18G-70-T-SFF

PL30122/2036

