



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**

Customer: _____ Tested By: Bryan K.
 SO No: _____ Temperature: +25°C
 Model No: PLDRO-12522R24M-13DBM-SFF Date: 12/2/2020
 Serial No: PL30785/2051 Drawing No: 27634480 Rev: B1


TEST ITEM	PARAMETERS	SPECIFIED VALUE		TEST RESULTS	QA QC
1	Frequency Range (fo)	12.52224 GHz		12.52224 GHz	PMI QA 2
2	External Reference	130.44 MHz		130.44 MHz	
3	Reference Input Power	0 ± 3 dBm		0 ± 3 dB	
4	Reference Phase Noise (SSB)	-122 dBc/Hz Min	100 Hz	(See Typical Characteristics)	
		-139 dBc/Hz Min	1 kHz		
		-153 dBc/Hz Min	10 kHz		
		-158 dBc/Hz Min	100 kHz		
5	Output Power	13 dBm Min		14.87dBm	
6	Spurious	-70 dBc Max In Band		-78.43dBc	
7	Harmonics	-20 dBc Max		-38.84dBc	
8	Phase Noise	-67 dBc/Hz Min	100 Hz	(See Typical Characteristics)	
		-96 dBc/Hz Min	1 kHz		
		-110 dBc/Hz Min	10 kHz		
		-115 dBc/Hz Min	100 kHz		
		-130 dBc/Hz Min	1 MHz		
9	DC Power	+12 to +15V @ 350 mA Max		+15 V @ 243 mA	
10	Lock Detect	TTL High In Lock		Pass	PMI QA 2

QA/QC Approval:  PMI QA 2  Date: 12/2/20



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**


Carrier Signal





**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**

Spurious





**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**

Ch Freq ----

Trig Free

Spurious Emissions

PASS

Spur	Range	Frequency	Amplitude	Limit
1	1	7.103 GHz	-63.56 dBm	-57.00 dBm
2	1	4.433 GHz	-64.23 dBm	-57.00 dBm
3	3	25.13 GHz	-71.95 dBm	-57.00 dBm
4	3	25.25 GHz	-73.75 dBm	-57.00 dBm
5	3	25.28 GHz	-73.76 dBm	-57.00 dBm
6	3	25.55 GHz	-73.87 dBm	-57.00 dBm
7	3	26.11 GHz	-74.01 dBm	-57.00 dBm
8	3	25.37 GHz	-74.05 dBm	-57.00 dBm
9	3	25.57 GHz	-74.06 dBm	-57.00 dBm
10	3	26.23 GHz	-74.14 dBm	-57.00 dBm
11	3	26.02 GHz	-74.28 dBm	-57.00 dBm
12	3	25.46 GHz	-74.31 dBm	-57.00 dBm

Emiss

Copyright 2000-2012 Agilent Technologies



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**

Harmonic

