



**SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM**

PL31033/2052

Customer: _____ Tested By: L. McGraw
SO No: _____ Temperature: +25°C
Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM Date: 12/21/2020
Serial No: PL31033/2052 Drawing No: 27630283 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	DC to 18 GHz	DC to 18 GHz See Plot	PMI QA 2
2	Isolation	60 dB Typ, 55 dB Min	62.6dB See Plot	
3	Insertion Loss:	4.5 dB Typ, 5.0 dB Max	3.7dB See Plot	
4	VSWR In/Out	2.0:1 Typ, 2.2:1 Max	1.8:1 See Plot	
5	Input Power	+17 dBm CW Max	Pass	
6	Switching Speed	6 ns Typ, 7 ns Max	7 ns See Typical Characteristics	
7	Rise/Fall Time	1 ns Typ, 2 ns Max	2 ns See Typical Characteristics	
8	Control Signal	TTL "1" On	Pass	
9	Video Transients	300 MHz BW (2 to 18 GHz) : 85 mV P-P 20 MHz BW (2 to 18 GHz) : 15 mV P-P	Pass	
10	DC Voltage	+8 to +15 V @ 15 mA Max -8 to -15 V @ 40 mA Max	+8 to +15 V @ 5 mA -8 to -15 V @ 28 mA	PMI QA 2

QA/QC Approval:  _____ PMI QA 2  Date: 12/23/20


7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com



**SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM**

PL31033/2052

(J1-J2) INSERTION LOSS AND RETURN LOSS



(J1-J2) ISOLATION AND RETURN LOSS

