



**SUMMARY TEST DATA  
ON  
PDC-2G18G-20C-SFF-50W**

Customer: \_\_\_\_\_

SO No: \_\_\_\_\_

Model No: PDC-2G18G-20C-SFF-50W

Serial No: PL31475/2108

Tested By: Bryan K.

Temperature: +25°C

Date: 2/20/2021

Drawing No: 27638200 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	2.0 to 18 GHz	2.0 to 18 GHz	PMI QA 2	
2	Insertion Loss (Excluding coupling loss 0.04 dB)	0.7 dB MAX.	0.42 dB (See Plot)		
3	VSWR	Primary: 1.40:1 MAX Secondary: 1.40:1 MAX	1.26:1 (See Plot)		
4	Directivity	15 dB MIN.	18.9 dB See Plot		
5	Coupling Factor	20 ± 0.7 dB MAX.	20.18 dB See Plot		
6	Coupling Sensitivity	±0.7 dB Over Frequency	±0.33 dB (See Plot)		
7	Power Handling	Incident: 50 Watts MAX Reflected: 2 Watts MAX	See Typical Characteristics		
8	Impedance	50 Ω	50 Ω		PMI QA 2

QA/QC Approval: \_\_\_\_\_

PMI  
QA 2

Date: \_\_\_\_\_

2/23/21



# SUMMARY TEST DATA ON PDC-2G18G-20C-SFF-50W

PL31475/2108

