

SUMMARY TEST DATA
ON
DTA-2G18G-60-12-CD-1-20DBM-TS-NSI

Customer: _____
Job No: _____
Model No: DTA-2G18G-60-12-CD-1-20DBM-TS-NSI
Serial No: PL33101/2130

Tested By: K. Mansfield
Date: Monday, June 10, 2024
Temperature: +25° C
Drawing No: 27617795 Rev: A2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	PASS/FAIL	QA QC	
1	Frequency Range:	2 GHz – 18 GHz	2 GHz – 18 GHz	PMI QA2	
2	Insertion Loss:	4.8 dB Max.	4.5 dB See Plot		
3	VSWR:	2.0:1 Max.	1.84:1 See Plot		
4	Flatness to 20 dB:	± 1.0 dB Typ.	0.6 dB See Plot		
6	Flatness to 40 dB:	± 1.25 dB Typ.	0.78 dB See Plot		
7	Flatness to 60 dB:	± 3.0 dB Typ.	1.33 dB See Plot		
8	Accuracy of Attenuation 0 to 20 dB:	± 1.0 dB Typ.	0.4 dB See Plot		
9	Accuracy of Attenuation 20 to 40 dB:	± 1.5 dB Typ.	0.93 dB See Plot		
10	Accuracy of Attenuation 40 to 60 dB:	± 2.0 dB Typ.	1.48 dB See Plot		
11	Temp. Sensor:	10mV/°C, 3.0V @ 25°C	2.98 V		
12	Switching Speed:	On Time: 1.0 µs Max. Off Time: 0.5 µs Max.	<1.0 µs On Time <0.5 µs Off Time See Typical Characteristics		
13	DC Supply:	+15VDC @ 150 mA Max.	120 mA		PMI QA2

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
0.015625	0.019357	-0.003732	0.00
0.03125	0.03642	-0.00517	0.00
0.0625	0.0619	0.0006	0.01
0.125	0.121	0.004	0.01
0.25	0.25	0.00	0.02
0.50	0.49	0.01	0.04
1.00	0.99	0.01	0.07
2.00	1.99	0.01	0.14
4.00	3.99	0.01	0.26
8.00	7.99	0.01	0.32
16.00	16.25	-0.77	0.44
32.00	32.77	-0.77	0.76

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
5.00	4.98	0.02	0.30
10.00	10.01	-0.01	0.32
15.00	15.07	-0.07	0.38
20.00	20.40	-0.40	0.60
25.00	25.54	-0.54	0.72
30.00	30.69	-0.69	0.78
35.00	35.80	-0.80	0.77
40.00	40.93	-0.93	0.74
45.00	46.05	-1.05	0.65
50.00	51.22	-1.22	0.58
55.00	56.37	-1.37	0.85
60.00	61.48	-1.48	1.33

QA/QC Approval: 

PMI
QA2

Date: 6/13/2024



