



SUMMARY TEST DATA ON DTA-2G18G-60-12-CD-1-20DBM-TS-NSI

Customer: _____
 Job No: _____
 Model No: DTA-2G18G-60-12-CD-1-20DBM-TS-NSI
 Serial No: PL33252/2130

Tested By: K. Mansfield
 Date: Saturday, July 31, 2021
 Temperature: +25° C
 Drawing No: 27617795 Rev: A2

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	PASS/FAIL	QA QC	
1	Frequency Range:	2 GHz – 18 GHz	2 GHz – 18 GHz	PMI QA 2	
2	Insertion Loss:	4.8 dB Max.	4.2 dB See Plot		
3	VSWR:	2.0:1 Max.	1.87:1 See Plot		
4	Flatness to 20 dB:	± 1.0 dB Typ.	0.77 dB See Plot		
6	Flatness to 40 dB:	± 1.25 dB Typ.	1.05 dB See Plot		
7	Flatness to 60 dB:	± 3.0 dB Typ.	1.22 dB See Plot		
8	Accuracy of Attenuation 0 to 20 dB:	± 1.0 dB Typ.	0.1 dB See Plot		
9	Accuracy of Attenuation 20 to 40 dB:	± 1.5 dB Typ.	0.04 dB See Plot		
10	Accuracy of Attenuation 40 to 60 dB:	± 2.0 dB Typ.	0.2 dB See Plot		
11	Temp. Sensor:	10mV/°C, 3.0V @ 25°C	3 V		
12	Switching Speed:	On Time: 1.0 µs Max. Off Time: 0.5 µs Max.	<1.0 µs On Time <0.5 µs Off Time See Typical Characteristics		
13	DC Supply:	+15VDC @ 150 mA Max.	120 mA		PMI QA 2

Programed Attenuation dB	Attenuation dB	Accuracy of Attenuation dB	Flatness dB ±dB
0.0156	0.0290	-0.01	0.01
0.0313	0.0396	-0.01	0.01
0.0625	0.0684	-0.01	0.01
0.125	0.128	0.00	0.02
0.25	0.25	0.00	0.03
0.50	0.50	0.00	0.05
1.00	1.01	-0.01	0.09
2.00	2.03	-0.03	0.17
4.00	4.07	-0.07	0.30
8.00	8.06	-0.06	0.33
16.00	16.00	-0.02	0.60
32.00	32.02	-0.02	0.97

Programed Attenuation dB	Attenuation dB	Accuracy of Attenuation dB	Flatness dB ±dB
5.00	5.06	-0.06	0.34
10.00	10.04	-0.04	0.35
15.00	14.90	0.10	0.53
20.00	20.00	0.00	0.77
25.00	24.96	0.04	0.97
30.00	30.00	0.00	1.05
35.00	35.02	-0.02	0.87
40.00	39.98	0.02	0.77
45.00	45.01	-0.01	0.76
50.00	50.09	-0.09	0.59
55.00	55.02	-0.02	0.85
60.00	60.20	-0.20	1.22

QA/QC Approval:

PMI
QA 2

Date: 8/12/2021



SUMMARY TEST DATA ON DTA-2G18G-60-12-CD-1-20DBM-TS-NSI

PL33252/2130

