



**SUMMARY TEST DATA
ON
P4T-500M40G-60-T-55-292FF-SP Rev. B**

Customer: _____
 SO No: _____
 Model No: P4T-500M40G-60-T-55-292FF-SP Rev. B
 Serial No: PL33286/2131

Tested By: A. Lopez
 Temperature: +25° C
 Date: 8/6/2021
 Drawing No: 27613629-B Rev: B2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC		
1	Frequency Range:	0.5 - 40 GHz	0.5 - 40 GHz	PMI QA 2		
2	Insertion Loss:	8.0 dB Max.	5.7 dB See Graph			
3	Isolation:	60 dB Min.	67 dB See Graph			
4	VSWR: In/Out	2.5:1 Max. 2.0:1 Typ.	2.18:1 In 2.18:1 Out See Graph			
5	Input Power:	+20 dBm CW Max.	Pass See Typical Characteristics			
6	Survival Power:	1 W Peak 1 μs	Pass See Typical Characteristics			
7	RF Switching Speed:	Rise/Fall: 15 ns Max. Delay On/Off 50 ns Max.	<15 ns Rise/Fall <50 ns Delay See Typical Characteristics			
8	DC Supply:	+5 VDC @ 250 mA Max. -5 VDC @ 100 mA Max.	+5 VDC @ 124 mA -5 VDC @ 60 mA			
9	Control Signal:	E1	E2		Function	Pass
		0	0	J1-J2 "Low Loss"		
		0	1	J1-J3 "Low Loss"		
		1	0	J1-J4 "Low Loss"		
		1	1	J1-J5 "Low Loss"		

QA/QC Approval:  _____
 PMI
QA 2

Date: 8/6/2021



SUMMARY TEST DATA ON P4T-500M40G-60-T-55-292FF-SP Rev. B

PL33286/2131

