



**SUMMARY TEST DATA
ON
P2T-2G6G-75-T-SFF-I**

Customer: _____
 SO No: _____
 Model No: P2T-2G6G-75-T-SFF-I
 Serial No: PL33485/2132

Tested By: K. Mansfield
 Temperature: +25°C
 Date: 8/13/2021
 Drawing No: 27635360 Rev: A2

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 GHz to 6.0 GHz	2.0 GHz to 6.0 GHz	PMI QA 2	
2	Insertion Loss:	1.5 dB Max.	1.5 dB See Plot		
3	Isolation:	85dB Typ. / 75dB Min.	89 dB See Plot		
4	Input VSWR:	2.0:1 Max.	In 1.3:1 See Plot		
5	Switching Speed:	100 ns Max.	<50 ns See Typical Characteristics		
6	Impedance:	50 Ω	50 Ω		
7	Input Power:	+30 dBm Max. (Survival) +20 dBm (Operating)	Pass		
8	DC Supply:	+5 VDC @ 100 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 27 mA -15 VDC @ 58 mA		PMI QA 2

LOGIC TABLE

GTL1	GTL2	J1 - J2	J1 - J3
0	0	ON	ON
0	1	ON	OFF
1	0	OFF	ON
1	1	OFF	OFF

QA/QC Approval: _____

PMI
QA 2

Date: 8/13/2021



**SUMMARY TEST DATA
ON
P2T-2G6G-75-T-SFF-I**

PL33485/2132

