



SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT812

Customer: _____

Tested By: K. Mansfield

SO No: _____

Temperature: +25° C

Model No: P1T-DC40G-65-T-292FF-1NS-OPT812

Date: 10/8/2021

Serial No: PL34254/2140

Drawing No: 27637740

Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	8 to 12 GHz	8 to 12 GHz	PMI QA 2	
2	Isolation:	70dB Typical, 60dB Min.	69dB See Plot		
3	Insertion Loss:	3.5dB Typical, 4.5dB Max.	3.44dB See Plot		
4	VSWR: In/Out	2.0:1 Typ, 2.2:1 Max.	1.34:1 In 1.3:1 Out See Plot		
5	Input Power:	+17 dBm CW Max.	+17 dBm		
6	Switching Speed:	3 ns Typ, 5 ns Max.	<5 ns See Typical Characteristics		
7	Rise/Fall Time:	0.9 ns Typ, 1.0 ns Max	<1 ns See Typical Characteristics		
8	Control Signal:	TTL "1" On	Pass		
9	DC Voltage:	+8 to +15 V @ 15 mA Max. -8 to -15 V @ 40 mA Max.	7 mA +V 27 mA -V		PMI QA 2

QA/QC Approval: _____

PMI
QA 2

Date: 10/8/2021



SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT812

PL34254/2140

