




SUMMARY TEST DATA
ON
P2T-1R2G1R4G-60-T-SFF

Customer: _____
 SO No: _____
 Model No: **P2T-1R2G1R4G-60-T-SFF**
 Serial No: **PL34333/2141**

Tested By: **Keith W.**
 Temperature: **+25°C**
 Date: **10/14/2021**
 Drawing No: **27630501** Rev: **A1**

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	1.2 GHz to 1.4 GHz	1.2 GHz to 1.4 GHz	PMI QA 2	
2	Insertion Loss:	1 dB Max.	0.97 dB (See Plot)		
3	VSWR:	1.5:1 Max.	In 1.21:1 Out 1.25:1 (See Plot)		
4	Isolation:	60 dB Min.	95 dB (See Plot)		
5	Switching Speed:	100 ns Max.	See Typical Characteristics		
6	Input Power:	+30 dBm Max. (Survival) +20 dBm Max. (Operating)	Pass See Typical Characteristics		
7	DC Supply:	+5 VDC @ 100 mA Max. -15 VDC @ 100 mA Max.	+5 VDC @ 22 mA -15 VDC @ 57 mA		
8	Control Signal:	LOGIC TABLE			Pass
		CTL1	Function		
		1	J1-J2 "Low Loss"		
0	J1-J3 "Low Loss"				

QA/QC Approval:  _____
 PMI
QA 2

Date: 10/15/2021

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com



SUMMARY TEST DATA
ON
P2T-1R2G1R4G-60-T-SFF

PL34333/2141

