



**SUMMARY TEST DATA
ON
P1T-DC18-60-T-SFF-HSLVT**

Customer: _____
 SO No: _____
 Model No: P1T-DC18-60-T-SFF-HSLVT
 Serial No: PL34421/2143

Tested By: Tin M. L
 Temperature: +25°C
 Date: 9/30/2021
 Drawing No: 27628081 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	DC to 18.0 GHz	DC to 18.0 GHz	PMI QA 2	
2	Insertion Loss:	4.5 dB Max.	3.7 dB		
3	Isolation:	60dB Min. (10 MHz - 12 GHz) 70 dB Min. (12 GHz - 18 GHz)	10 Mhz - 12 GHz: 62 dB 12 GHz - 18 GHz: 80.7 dB		
4	VSWR:	2.0:1 Max.	1.7:1		
5	DC Supply:	-5VDC @ 25 mA Typ.	-5VDC @ 25 mA		
6	Control Signal:	TTL Logic "0" = ON TTL Logic "1" = OFF	Pass		PMI QA 2

QA/QC Approval: _____

PMI
QA 2

Date: 10/29/2021



**SUMMARY TEST DATA
ON
P1T-DC18-60-T-SFF-HSLVT**

PL34421/2143

