



**SUMMARY TEST DATA
ON
P1T-218-60-515-R-SFF**

Customer: _____
 SO No: _____
 Model No: P1T-218-60-515-R-SFF
 Serial No: PL34810/2147

Tested By: John R
 Temperature: +25° C
 Date: 11/29/2021
 Drawing No: 27641600 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	2 GHz to 18 GHz	2 GHz to 18 GHz	PMI QA 2	
2	Isolation	60 dB Min.	68.4 dB		
3	Insertion Loss	1.8 dB Max.	1.72 dB		
4	VSWR: In/Out	1.9:1 Max.	1.47:1 In 1.47:1 Out		
5	Input Power	33 dBm CW Max	20 dBm CW		
6	DC SUPPLY	+5VDC @ 65 mA Max. -15VDC @ 65 mA Max.	+5VDC @ 21 mA -15VDC @ 25 mA		
7	Control Signal	TTL LOGIC "0" : Insertion Loss "1" : Isolation E1 : J1-J2	PASS		PMI QA 2

QA/QC Approval: 

PMI
QA 2

Date: 11/30/2021



SUMMARY TEST DATA ON P1T-218-60-515-R-SFF

PL34810/2147

