



**SUMMARY TEST DATA
ON
P1T-DC18-60-T-SFF-HSLVT**

Customer: _____

SO No: _____

Model No: P1T-DC18-60-T-SFF-HSLVT

Serial No: PL34890/2148

Tested By: L. McGraw

Temperature: +25° C

Date: 11/30/2021

Drawing No: 27628081

Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0 GHz to 18 GHz	0 GHz to 18 GHz	PMI QA1
2	Insertion Loss	4.5 dB Max.	3.6 dB	
3	Isolation	60 dB Min. (10 MHz - 12 GHz) 70 dB Min. (12 MHz - 18 GHz)	10 MHz - 12 GHz: 60.9 dB 12 GHz - 18 GHz: 76.2 dB	
4	VSWR: In/Out	2:1 Max.	1.72:1 In 1.74:1 Out	
5	DC SUPPLY	-5VDC @ 25 mA Max.	-5VDC @ 20mA	
6	Control Signal	TTL LOGIC '0' : Insertion Loss '1' : Isolation	PASS	PMI QA1

QA/QC Approval: _____

PMI
QA1

Date: _____

11/30/21



SUMMARY TEST DATA ON P1T-DC18-60-T-SFF-HSLVT

PL34890/2148

