



**SUMMARY TEST DATA  
ON  
P1T-6G18G-60-T-SFF-1W**

Customer: \_\_\_\_\_  
SO No: \_\_\_\_\_  
Model No: P1T-6G18G-60-T-SFF-1W  
Serial No: PL35365/2203

Tested By: John R.  
Temperature: +25°C  
Date: 1/18/2022  
Drawing No: 27628521 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	6.0 GHz to 18.0 GHz	6.0 GHz to 18.0 GHz	PMI QA 2	
2	Insertion Loss:	2.75 dB Max.	2.5 dB (See Plot)		
3	Isolation:	65 dB Min.	70 dB (See Plot)		
4	VSWR:	2.0:1 Max. (1.5:1 Goal)	In 1.66:1 Out 1.58 :1 (See Plot)		
5	Switching Speed:	25 ns Typ.	25 ns Typ. See Typical Characteristics		
6	Operating Power:	+30 dBm Max.	Pass See Typical Characteristics		
7	DC Supply:	+5 VDC @ 50 mA Max. -15 VDC @ 75 mA Max.	+5 VDC @ 23 mA -15 VDC @ 57 mA		
8	Control Signal:	TTL "0" → (Insertion Loss) TTL "1" → (Isolation)	Pass		PMI QA 2

QA/QC Approval: \_\_\_\_\_

PMI  
QA 2

Date: \_\_\_\_\_

1/20/2022



**SUMMARY TEST DATA  
ON  
P1T-6G18G-60-T-SFF-1W**

PL35365/2203

