



SUMMARY TEST DATA
ON
P2T-2G18G-55-T-512-SFF-LV-SP-QB

Customer: _____
 SO No: _____
 Model No: P2T-2G18G-55-T-512-SFF-LV-SP-QB
 Serial No: PL35399/2204

Tested By: S. O'Neill
 Temperature: +25°C
 Date: 6/12/2023
 Drawing No: 27633620 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2.0 GHz - 18.0 GHz	2.0 GHz - 18.0 GHz	PMI QA2
2	Insertion Loss:	3.0 dB Max.	2.89 dB See Plot	
3	Isolation:	55 dB Min.	68 dB See Plot	
4	VSWR:	2.0:1 Max.	In 1.86:1 Out 1.89 :1 See Plot	
5	Input Power:	+23 dBm CW Max. (Oper.) +27 dBm CW Max. (Surv.)	+23 dBm CW Max. (Oper.) +27 dBm CW Max. (Surv.) See Typical Characteristics	
6	Switching Speed:	50nsec Max Ton = 50% TTL to 90% RF Toff = 50% TTL to 10% RF	50nsec Max Ton = 50% TTL to 90% RF Toff = 50% TTL to 10% RF See Typical Characteristics	
7	Switching Rate PRF:	5 MHz	5 MHz See Typical Characteristics	
8	Video Leakage:	50 mV Peak to Peak Max. Measured @ 300 MHz BW	50 mV Peak to Peak Max. Measured @ 300 MHz BW See Typical Characteristics	
9	Control Logic:	"0" = Insertion Loss (1.6mA Max. Sink @ 0.4V) "1" = Isolation (40µA Max. Source @ 2.4V)	"0" = Insertion Loss (1.6mA Max. Sink @ 0.4V) "1" = Isolation (40µA Max. Source @ 2.4V)	
10	DC Supply:	+5 VDC - 80 mA -12 VDC - 80 mA	+5 VDC @ 22 mA -12 VDC @ 68 mA	

QA/QC Approval: _____

[Handwritten Signatures]

PMI
QA2

Date: 6/19/2023



SUMMARY TEST DATA
ON
P2T-2G18G-55-T-512-SFF-LV-SP-QB

PL35399/2204

