



# SUMMARY TEST DATA ON P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM  
 Serial No: PL37360/2230

Tested By: E. Kretz  
 Temperature: +25°C  
 Date: 10/6/2023  
 Drawing No: 27630283 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	DC to 18 GHz	DC to 18 GHz	PMI QA1
2	Isolation:	60 dB Typ. 55 dB Min.	60 dB See Graph	
3	Insertion Loss:	4.5 dB Typ 5.0 dB Max.	4.08 dB See Graph	
4	VSWR: In/Out	2.0:1 Typ. 2.2:1 Max.	In 2.01:1 Out 1.75 :1 See Graph	
5	Input Power:	+17 dBm CW Max.	Pass See Typical Characteristics	
6	Switching Speed:	6 ns Typ. 7 ns Max.	Pass See Typical Characteristics	
7	Rise/Fall Time:	1 ns Typ. 2 ns Max.	Pass See Typical Characteristics	
8	Control Signal:	TTL "1" On Internally Terminated to 50 Ω	Pass	
9	Video Transients:	300 MHz BW (2 to 18 GHz): 85 mV P-P 20 MHz BW (2 to 18 GHz): 15 mV P-P	Pass See Typical Characteristics	
10	DC Supply:	+8 to +15 V @ 15 mA Max. -8 to -15 V @ 40 mA Max.	+8 to +15 V @ 12 mA -8 to -15 V @ 27 mA	PMI QA1

QA/QC Approval: \_\_\_\_\_

PMI  
QA1

Date: \_\_\_\_\_

10/13/23



# SUMMARY TEST DATA ON P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM

PL37360/2130

