



**SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM**

PL37368/2230

Customer: _____ Tested By: L. McGraw
SO No: _____ Temperature: +25°C
Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM Date: 07/29/21
Serial No: PL37368/2230 Drawing No: 27630283 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	DC to 18 GHz	DC to 18 GHz See Plot	PMI QA 2
2	Isolation	60 dB Typ, 55 dB Min	61dB See Plot	
3	Insertion Loss:	4.5 dB Typ, 5.0 dB Max	4.0dB See Plot	
4	VSWR In/Out	2.0:1 Typ, 2.2:1 Max	1.9:1 See Plot	
5	Input Power	+17 dBm CW Max	Pass	
6	Switching Speed	6 ns Typ, 7 ns Max	2.7ns See Typical Characteristics	
7	Rise/Fall Time	1 ns Typ, 2 ns Max	0.6ns See Typical Characteristics	
8	Control Signal	TTL "1" On	Pass	
9	Video Transients	300 MHz BW (2 to 18 GHz) : 85 mV P-P 20 MHz BW (2 to 18 GHz) : 15 mV P-P	Pass	
10	DC Voltage	+8 to +15 V @ 15 mA Max -8 to -15 V @ 40 mA Max	+8 to +15 V @ 6 mA -8 to -15 V @ 27 mA	PMI QA 2

QA/QC Approval:  PMI QA 2 Date: 8/8/2022


7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com




**SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM**

PL37368/2230

Insertion Loss and Return Loss (J1 – J2)



Isolation and Termination (J1 – J2)



7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com