

**SUMMARY TEST DATA  
ON  
P2T-2G4G-80-55-R-SFF**

Customer: \_\_\_\_\_

Tested By: L. McGraw

SO No: \_\_\_\_\_

Temperature: +25°C

Model No: P2T-2G4G-80-55-R-SFF

Date: 8/23/2022

Serial No: PL37572/2234

Drawing No: 27644400 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 GHz to 4.0 GHz	2.0 GHz to 4.0 GHz	PMI QA 2	
2	Insertion Loss:	1.3 dB Max.	1.17 dB See Plot		
3	Isolation:	80 dB Min.	81 dB See Plot		
4	VSWR:	1.5:1 Max.	1.2:1 See Plot		
5	Switching Speed:	50 ns Max.	See Typical Characteristics		
6	Operational Input Power:	+30 dBm Max.	See Typical Characteristics		
7	DC Supply:	+5 VDC 100 mA Max. -5 VDC 50 mA Max.	+5 VDC @ 14 mA -5 VDC @ 9 mA		
8	Control:	TTL "0" → (J0-J2) TTL "1" → (J0-J3)	Pass		PMI QA 2

QA/QC Approval:  \_\_\_\_\_

Date: 8/23/2022

