



**SUMMARY TEST DATA
ON
P2T-1R2G1R4G-60-T-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-1R2G1R4G-60-T-SFF
 Serial No: PL38040/2239

Tested By: John R.
 Temperature: +25°C
 Date: 9/30/2022
 Drawing No: 27635360 Rev: A2

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	1.2 GHz to 1.4 GHz	1.2 GHz to 1.4 GHz	PMI QA1
2	Insertion Loss:	1.0 dB Max.	0.83 dB See Plot	
3	Isolation:	60dB Min.	85 dB Min. See Plot	
4	Input VSWR:	1.5:1 Max.	In 1.19:1 Out 1.25:1 See Plot	
5	Switching Speed:	100 ns Max.	<50 ns See Typical Characteristics	
6	Impedance:	50 Ω	50 Ω	
7	Input Power:	+30 dBm Max. (Survival) +20 dBm (Operating)	Pass	
8	DC Supply:	+5 VDC @ 100 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 24 mA -15 VDC @ 56 mA	

LOGIC TABLE

CTL1	J1-J2	J1-J3
0	ON	OFF
1	OFF	ON

QA/QC Approval: _____

PMI
QA1

Date: _____

9/30/22



SUMMARY TEST DATA ON P2T-1R2G1R4G-60-T-SFF

PL38040/2239

