



**SUMMARY TEST DATA
ON
P2T-1R2G1R4G-60-T-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-1R2G1R4G-60-T-SFF
 Serial No: PL38044/2239

Tested By: John R.
 Temperature: +25°C
 Date: 9/30/2022
 Drawing No: 27635360 Rev: A2

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	1.2 GHz to 1.4 GHz	1.2 GHz to 1.4 GHz	PMI QA1	
2	Insertion Loss:	1.0 dB Max.	0.83 dB See Plot		
3	Isolation:	60dB Min.	86 dB Min. See Plot		
4	Input VSWR:	1.5:1 Max.	In 1.17:1 Out 1.2:1 See Plot		
5	Switching Speed:	100 ns Max.	<50 ns See Typical Characteristics		
6	Impedance:	50 Ω	50 Ω		
7	Input Power:	+30 dBm Max. (Survival) +20 dBm (Operating)	Pass		
8	DC Supply:	+5 VDC @ 100 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 24 mA -15 VDC @ 56 mA		PMI QA1

LOGIC TABLE

CTL1	J1-J2	J1-J3
0	ON	OFF
1	OFF	ON

QA/QC Approval: _____

PMI
QA1

Date: _____

9/30/22

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com



SUMMARY TEST DATA ON P2T-1R2G1R4G-60-T-SFF

PL38044/2239

