



**SUMMARY TEST DATA
ON
PDC-418-20-50W-SFF**

Customer: _____
SO No: _____
Model No: PDC-418-20-50W-SFF
Serial No: PL38141/2241

Tested By: Tin M. L
Temperature: +25°C
Date: 10/10/2022
Drawing No: 27040180 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	4 TO 18 GHz	4 TO 18 GHz	PMI QA2	
2	Insertion Loss:	0.7 dB MAX (Excluding Coupled Power 0.04dB)	0.36 dB (See Plot)		
3	Coupling Factor:	20 ±0.7 dB MAX.	20 ±0.34 dB See Plot		
4	Coupling Sensitivity:	±0.7 dB MAX.	±0.31 dB (See Plot)		
5	Directivity:	12 dB MIN.	37.1 dB See Plot		
6	VSWR:	Primary 1.4:1 MAX. Secondary 1.4:1 MAX.	1.2:1 1.21:1 (See Plot)		
7	Power Handling:	Incident ≤ 50 W Reflected ≤ 2 W	Pass Typical Characteristics		
8	Impedance:	50 Ω	Pass		PMI QA2

QA/QC Approval: 



PMI
QA2

Date: 10/10/2022



SUMMARY TEST DATA
ON
PDC-418-20-50W-SFF

PL38141/2241





**SUMMARY TEST DATA
ON
PDC-418-20-50W-SFF**

PL38141/2241

