



SUMMARY TEST DATA ON LM-10M14G-100W-1KWP-SFF-OPT17

Customer: _____
 SO No: _____
 Model No: LM-10M14G-100W-1KWP-SFF-OPT17
 Serial No: PL38547/2247

Tested By: K Craven
 Temperature: +25°C
 Date: 11/23/2022
 Drawing No: 27636460 REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC	
1	Frequency Range:	10 MHz to 7 GHz	10 MHz to 7 GHz	PMI QA2	
2	Insertion Loss:	2 dB Typ.	1.15 dB See Graph		
3	Input/Output VSWR:	2.0:1 Max. (@ -10 dBm Input)	Input 1.74:1 Output 1.8:1 See Graph		
4	Impedance:	50 Ω	Pass		
5	Max. CW Input Power:	100W CW Max. (1.0 GHz to 7.0 GHz) All Temperatures (-55°C to +85°C)	Pass See Typical Characteristics		
6	Max. Pulsed Peak Power Handling:	1KW Peak (1% Duty Cycle, 1µs Pulse Width) 100W Peak (10% Duty Cycle, 10µs Pulse Width)	Pass See Typical Characteristics		
7	Max. Flat Leakage:	+17 dBm Typ. (At 100W CW)	Pass See Typical Characteristics		
8	P1dB:	+ 5 dBm Min.	+ 7 dBm See Graph		
9	Recovery Time:	100 ns Max.	Pass See Typical Characteristics		PMI QA2

QA/QC Approval:  PMI QA2

Date: 11/23/2022

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
 Email: sales@pmi-rf.com

**SUMMARY TEST DATA
 ON
 LM-10M14G-100W-1KWP-SFF-OPT17**

