



SUMMARY TEST DATA
ON
P3T-1G18G-65-T-SFF

Customer: _____
 SO No: _____
 Model No: P3T-1G18G-65-T-SFF
 Serial No: PL38881/2250

Tested By: S. O'Neill
 Temperature: +25°C
 Date: 2/4/2025
 Drawing No: 27626641 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC		
1	Frequency Range:	1.0 to 18.0 GHz	1.0 to 18.0 GHz	PMI QA2		
2	Insertion Loss:	3.75 dB Max.	2.96 dB See Plot			
3	Isolation:	60 dB Min.	74 dB See Plot			
4	VSWR: In/Out	2.0:1 Max.	In 1.76:1 Out 1.72 :1 See Plot			
5	Switching Speed:	100 ns Max.	< 100 ns See Typical Characteristics			
6	Input Power:	+30 dBm Max. (Survival) +20 dBm Max. (Operating)	Pass See Typical Characteristics			
7	DC Supply:	+5 VDC @ 150 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 27 mA -15 VDC @ 58 mA			
8	Control Signal:	Logic Table			Pass	
		E1	E2	E3		Function
		0	1	1		J1-J2 "Low Loss"
		1	0	1		J1-J3 "Low Loss"
		1	1	0	J1-J4 "Low Loss"	
					PMI QA2	

QA/QC Approval: _____

PMI
QA2

Date: 3/3/2025



SUMMARY TEST DATA
ON
P3T-1G18G-65-T-SFF

PL38881/2250

