



SUMMARY TEST DATA ON P2T-2G18G-55-T-512-SFF-LV-SP-QB

Customer: _____
 SO No: _____
 Model No: P2T-2G18G-55-T-512-SFF-LV-SP-QB
 Serial No: PL39767/2309

Tested By: John R.
 Temperature: +25°C
 Date: 3/15/2023
 Drawing No: 27633620 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 GHz - 18.0 GHz	2.0 GHz - 18.0 GHz	PMI QA1	
2	Insertion Loss:	3.0 dB Max.	2.86 dB See Graph		
3	Isolation:	55 dB Min.	67.3 dB See Graph		
4	VSWR:	2.0:1 Max.	1.95:1 In 1.94 :1 Out See Graph		
5	Input Power:	+23 dBm CW Max. (Oper.) +27 dBm CW Max. (Surv.)	+23 dBm CW Max. (Oper.) +27 dBm CW Max. (Surv.) See Typical Characteristics		
6	Switching Speed:	50nsec Max Ton = 50% TTL to 90% RF Toff = 50% TTL to 10% RF	50nsec Max Ton = 50% TTL to 90% RF Toff = 50% TTL to 10% RF See Typical Characteristics		
7	Switching Rate PRF:	5 MHz	5 MHz See Typical Characteristics		
8	Video Leakage:	50 mV Peak to Peak Max. Measured @ 300 MHz BW	50 mV Peak to Peak Max. Measured @ 300 MHz BW See Typical Characteristics		
9	Control Logic:	"0" = Insertion Loss (1.6mA Max. Sink @ 0.4V) "1" = Isolation (40µA Max. Source @ 2.4V)	"0" = Insertion Loss (1.6mA Max. Sink @ 0.4V) "1" = Isolation (40µA Max. Source @ 2.4V)		
10	DC Supply:	+5 VDC @ 80 mA -12 VDC @ 80 mA	+5 VDC @ 36 mA -12 VDC @ 68 mA		PMI QA1

QA/QC Approval: PMI QA1 Date: 3/17/23

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
 Email: sales@pmi-rf.com

**SUMMARY TEST DATA
ON
P2T-2G18G-55-T-512-SFF-LV-SP-QB**

