

SUMMARY TEST DATA ON P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM

Customer: _____
 SO No: _____
 Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM
 Serial No: PL39958/2311

Tested By: K. Wagaman
 Temperature: +25 °C
 Date: 3/17/2023
 Drawing No: 27630283 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	DC to 18 GHz	DC to 18 GHz	PMI QA2
2	Isolation:	60 dB Typ. 55 dB Min.	60 dB See Graph	
3	Insertion Loss:	4.5 dB Typ 5.0 dB Max.	3.83 dB See Graph	
4	VSWR: In/Out	2.0:1 Typ. 2.2:1 Max.	In 1.85:1 Out 1.98 :1 See Graph	
5	Input Power:	+17 dBm CW Max.	Pass See Typical Characteristics	
6	Switching Speed:	6 ns Typ. 7 ns Max.	Pass See Typical Characteristics	
7	Rise/Fall Time:	1 ns Typ. 2 ns Max.	Pass See Typical Characteristics	
8	Control Signal:	TTL "1" On Internally Terminated to 50 Ω	Pass	
9	Video Transients:	300 MHz BW (2 to 18 GHz): 85 mV P-P 20 MHz BW (2 to 18 GHz): 15 mV P-P	Pass See Typical Characteristics	
10	DC Supply:	+8 to +15 V @ 15 mA Max. -8 to -15 V @ 40 mA Max.	+8 to +15 V @ 12 mA -8 to -15 V @ 27 mA	PMI QA2

QA/QC Approval: 

PMI
QA2

Date: 3/17/2023

**SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM**

