

**SUMMARY TEST DATA
ON
APD-2-0518-YR1 Rev. B**

Customer: _____
 SO No: _____
 Model No: APD-2-0518-YR1 Rev. B
 Serial No: PL40241/2317

Tested By: K. Wagaman
 Temperature: +25°C
 Date: 4/24/2023
 Drawing No: 27610310 Rev: A3

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS		QA QC
			J2	J3	
1	Frequency Range:	0.5 GHz - 18.0 GHz	0.5 GHz - 18.0 GHz		PMI QA2
2	Insertion Loss:	(0.5 to 8.0 GHz) 1.85 dB Typ. (8.0 to 18.0 GHz) 3.5 dB Typ.	1.84 dB 3.29 dB See Plot	1.95 dB 3.46 dB See Plot	
3	VSWR:	(0.5 to 8.0 GHz) 1.5:1 Typ. (8.0 to 18.0 GHz) 1.6:1 Typ.	1.45:1 1.44 :1 See Plot	1.45:1 1.49 :1 See Plot	
4	Isolation:	(0.5 to 8.0 GHz) 16.5 dB Typ. (8.0 to 18.0 GHz) 21.0 dB Typ.	-17.47 dB -20.89 dB See Plot		
5	Amplitude Balance:	(0.5 to 8.0 GHz) ±0.2 dB Typ. (8.0 to 18.0 GHz) ±0.45 dB Typ.	0.08 dB 0.01 dB See Plot		
6	Phase Balance:	(0.5 to 8.0 GHz) ±4° Typ. (8.0 to 18.0 GHz) ±5° Typ.	0.8° / -0.38° 2.35° / 0.48° See Plot		

QA/QC Approval:  PMI QA2

Date: 4/24/2023

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com



