



SUMMARY TEST DATA ON LM-10M2D5G-100CW-1KWP-SFF

Customer: _____
 SO No: _____
 Model No: LM-10M2D5G-100CW-1KWP-SFF
 Serial No: PL40413/2317

Tested By: John R.
 Temperature: +25°C
 Date: 4/28/2023
 Drawing No: 27624585 REV: A5

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	10 MHz to 2.5 GHz	10 MHz to 2.5 GHz	<i>PMI</i> <i>QA2</i> <hr style="border: 1px solid blue;"/>
2	Insertion Loss:	0.8 dB Max.	0.53 dB See Graph	
3	Input/Output VSWR:	1.3:1 Max. @ -10 dBm Input (Notes 1,2)	1.17:1 In 1.13:1 Out See Graph	
4	Impedance:	50 Ω	Pass	
5	Input Power:	100W CW Maximum 1KW Peak (1% DUTY CYCLE, 1uS Maximum Pulse Width) (Notes 1,2,3,4)	Pass See Typical Characteristics	
6	Flat Leakage:	+14 dBm Max. @ 10W CW	Pass See Typical Characteristics	
7	P1dB:	0 dBm Min.	+ 7 dBm See Graph	
8	Recovery Time:	2 uS Typ.	Pass See Typical Characteristics	

Notes:

1. POWER RATING AT 25°C: DERATED LINEARLY TO ZERO AT 150°C
2. HIGH POWER TEST DURATION: FULL RATED POWER FOR 10 SECONDS
3. HIGH POWER PEAK CONDITIONS: 1KW PEAK (1% DUTY CYCLE, 1USEC MAXIMUM PULSE WIDTH)
4. EXTERNAL DC BLOCKS ARE REQUIRED FOR PROPER FUNCTION.

QA/QC Approval: _____

PMI
QA2

Date: _____

4/28/2023

**SUMMARY TEST DATA
ON
LM-10M2D5G-100CW-1KWP-SFF**

