

**SUMMARY TEST DATA
ON
P8T-20M18G-80-R-512-SFF**

Customer:

SO No: _____

Tested By: S. O'Neill

Temperature: +25° C

Model No: P8T-20M18G-80R-512-SFF


Date: 6/15/2023

Serial No: PL40973/2324

Drawing No: 27616149

Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	0.012 GHz to 18 GHz	0.012 GHz to 18 GHz	PMI QA2	
2	Isolation	80 dB Min.	83.2 dB		
3	Insertion Loss	4.5 dB Max. 4 dB Typ.	3.6 dB		
4	VSWR: In/Out	2:1 Max.	1.8:1 In 1.84:1 Out		
5	Input Power	23 dBm CW Max.	Pass See Typical Characteristics		
6	DC SUPPLY	+5VDC @ 300 mA Max. -12VDC @ 100 mA Max.	+5VDC @ 269 mA -12VDC @ 92 mA		
7	Switching Speed	1000 ns Max.	Pass See Typical Characteristics		PMI QA2



QA/QC Approval: *[Signature]* PMI QA2

Date: 6/15/2023

**SUMMARY TEST DATA
ON
P8T-20M18G-80-R-512-SFF**

