



SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS

Customer: _____
 SO No: _____
 Model No: P1T-DC40G-65-T-292FF-1NS
 Serial No: PL41388/2330

Tested By: S. O'Neill
 Temperature: +25° C
 Date: 7/12/2024
 Drawing No: 27621866 Rev: A3

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	DC to 40 GHz	DC to 40 GHz	PMI QA2	
2	Isolation:	65 dB Typ, 55 dB Min.	59 dB See Plot		
3	Insertion Loss:	5.5 dB Typ, 6.8 dB Max.	5.99 dB See Plot		
4	VSWR: In/Out	2.0:1 Typ, 2.2:1 Max.	2.01:1 In 2.05:1 Out See Plot		
5	Input Power:	+17 dBm CW Max.	+17 dBm		
6	Switching Speed:	5 ns Typ, 6 ns Max.	<3 ns See Typical Characteristics		
7	Rise/Fall Time:	0.9 ns Typ, 1.0 ns Max	<0.7 ns See Typical Characteristics		
8	Control Signal:	TTL "1" On	Pass		
9	DC Voltage:	+8 to +15 V @ 15 mA Max. -8 to -15 V @ 400 mA Max.	8 mA +V 26 mA -V		PMI QA2

QA/QC Approval: PMI
QA2

Date: 7/15/2024



SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS

PL41388/2330

