



**SUMMARY TEST DATA  
ON  
LM-1G18G-15-3W-500WP-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: LM-1G18G-15-3W-500WP-SFF  
 Serial No: PL41417/2330  
 Part No: \_\_\_\_\_

Tested By: John R.  
 Temperature: +25°C  
 Date: 7/26/2023  
 Drawing No: 27634041      REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	1.0 to 18.0 GHz	1.0 to 18.0 GHz	PMI QA2
2	Insertion Loss:	2.5 dB Max. @ -20 dBm Input Power	2.31 dB See Graph	
3	Recovery Time:	100 ns Typical	Pass See Typical Characteristics	
4	VSWR:	2.0:1 Max. @ -20 dBm Input Power	1.82:1 In 1.87:1 Out See Graph	
5	RF Power Handling:	3 W CW Max.	Pass See Typical Characteristics	
		500W Peak Max. (1 µs PW, 0.1% DC)	Pass See Typical Characteristics	
6	Limiting Threshold:	+17 dBm Typ. (1 dB Compression)	+12 dBm See Graph	

QA/QC Approval:  PMI  
QA2

Date: 7/26/2023

**SUMMARY TEST DATA  
ON  
LM-1G18G-15-3W-500WP-SFF**

