



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF-ROHS**

PL41461/2330

Customer: _____ Tested By: K Craven
SO No: _____ Temperature: +25°C
Model No: PLDRO-12522R24M-13DBM-SFF-ROHS Date: 6/19/24
Serial No: PL41461/2330 Drawing No: 27634480 Rev: B1

TEST ITEM	PARAMETERS	SPECIFIED VALUE		TEST RESULTS	QA QC
1	Frequency Range (fo)	12.52224 GHz		12.52224 GHz	PMI QA4
2	External Reference	130.44 MHz		130.44 MHz	
3	Reference Input Power	0 ± 3 dBm		0 ± 3 dB	
4	Output Power	13 dBm Min		15.42 dBm	
5	Spurious	-70 dBc Max In Band		-79.80 dBc	
6	Harmonics	-20 dBc Max		-44.70 dBc	
7	Phase Noise	-67 dBc/Hz Min	100 Hz	See Plot	
		-96 dBc/Hz Min	1 kHz		
		-110 dBc/Hz Min	10 kHz		
		-115 dBc/Hz Min	100 kHz		
		-130 dBc/Hz Min	1 MHz		
8	DC Power	+12 to +15V @ 350 mA Max		+15 @ 210 mA	
9	Lock Detect	TTL High In Lock		Pass	PMI QA4


QA/QC Approval: Cammeren Kelley Date: 6/21/24




SUMMARY TEST DATA ON PLDRO-12522R24M-13DBM-SFF-ROHS

PL41461/2330

Carrier Signal



Harmonics



Frequency	Amplitude
1 12.52 GHz	15.43 dBm
2 25.04 GHz	-46.84 dBc
3 37.57 GHz	-48.10 dBc
4 50.09 GHz	-44.70 dBc




SUMMARY TEST DATA ON PLDRO-12522R24M-13DBM-SFF-ROHS

PL41461/2330

Spurious

✱ Agilent



□

Phase Noise Curve

