



**SUMMARY TEST DATA
ON
P2T-500M18G-80-T-515-SFF-4W-ST**

Customer: _____
 SO No: _____
 Model No: P2T-500M18G-80-T-515-SFF-4W-ST
 Serial No: PL41651/2332

Tested By: L. McGraw
 Temperature: +25°C
 Date: 8/3/2023
 Drawing No: 27624523 Rev: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	0.5 to 18.0 GHz	0.5 to 18.0 GHz	PMI QA2
2	Insertion Loss:	3.5 dB Typ.	3 dB See Plot	
3	Isolation:	70 dB Min.	77 dB See Plot	
4	VSWR:	2.0:1 Max.	1.69:1 See Plot	
5	Operating Input Power:	4 Watts CW Max.	Pass See Typical Characteristics	
6	Switching Speed:	60 ns Max.	<40 ns See Typical Characteristics	
7	Power Supply:	+5 VDC @ 150 mA -15 VDC @ 150 mA	+5 VDC @ 60 mA -15 VDC @ 79 mA	
8	Control:	Logic Table		
		CTL1	Function	
		1	J1 - J2	
		0	J1 - J3	Pass

QA/QC Approval: PMI
QA2

Date: 8/4/2023

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com



SUMMARY TEST DATA ON P2T-500M18G-80-T-515-SFF-4W-ST

PL41651/2332

